

FORMAL PUBLIC IDENTIFIER

```
<!DOCTYPE html
PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd">
```

DOCUMENT STRUCTURE

html

CM: (head, body)
AT: %i18;, id, xmlns

DOCUMENT HEAD

%head.misc

(script | style | meta | link | object | isindex)

head

CM: (%head.misc,
((title, %head.misc,
(base, %head.misc)? |
(base, %head.misc;
(title, %head.misc))))
AT: %i18n;, id, profile

title

CM: (#PCDATA)
AT: %i18n;, id

base

CM: EMPTY
AT: id, href, target

meta

CM: EMPTY
AT: %i18n;, id, http-equiv, name, content, scheme

link

CM: EMPTY
AT: %attrs;, charset, href, hreflang, type, rel, rev, media, target

style

CM: (#PCDATA)
AT: %i18n;, id, type, media, title, xml:space

script

CM: (#PCDATA)
AT: id, charset, type, language, src, defer, xml:space

noscript

CM: (%Flow;)
AT: %attrs;

FRAMES

frameset

CM: (frameset | frame | noframes)
AT: %coreattrs;, rows, cols, onload, onunload

frame

CM: EMPTY
AT: %coreattrs;, longdesc, name, src, frameborder, marginwidth, marginheight, noresize, scrolling

iframe

CM: (%Flow;)
AT: %coreattrs;, longdesc, name, src, frameborder, marginwidth, marginheight, scrolling, align, height, width

noframes

CM: (body)
AT: %attrs;

DOCUMENT BODY

body

CM: (%Flow;)
AT: %attrs;, onload, onunload, background, bgcolor, text, link, vlink, alink

div

CM: (%Flow;)
AT: %attrs;, %TextAlign;

PARAGRAPHS

p

CM: (%Inline;)
AT: %attrs;, %TextAlign;

HEADINGS

h1, h2, h3, h4, h5, h6

CM: (%Inline;)
AT: %attrs;, %TextAlign;

ADDRESS

address

CM: (#PCDATA | %inline; | %misc.inline | p)
AT: %attrs;

LISTS

ul

CM: (li)+
AT: %attrs;, type, compact

dl

CM: (dt | dd)+
AT: %attrs;, compact

ol

CM: (li)+
AT: %attrs;, type, compact, start

dt

CM: (%Inline;)
AT: %attrs;

menu, dir

CM: (li)+
AT: %attrs;, compact

dd

CM: (%Flow;)
AT: %attrs;

li

CM: (%Flow;)
AT: %attrs;, type, value

HORIZONTAL RULE

hr

CM: EMPTY
AT: %attrs;, align, noshade, size, width

PREFORMATTED TEXT

pre

CM: (%pre.content;)
AT: %attrs;, width, xml:space

TEXT ALIGNMENT

center

CM: (%Flow;)
AT: %attrs;

BLOCK-LIKE QUOTES

blockquote

CM: (%Flow;)
AT: %attrs;, cite

INSERTED/DELETED TEXT

ins, del

CM: (%Flow;)
AT: %attrs;, cite, datetime

INLINE ELEMENTS

span, em, strong, dfn, code, samp, kbd, var, cite, abbr, acronym, sub, sup, tt, i, b, big, small, u, s, strike

CM: (%Inline;)
AT: %attrs;

q

CM: (%Inline;)
AT: %attrs;, cite

basefont

CM: EMPTY
AT: id, size, color, face

font

CM: (%Inline;)
AT: %coreattrs;, %i18n;, size, color, face

br

CM: EMPTY
AT: %coreattrs;, clear

ANCHOR ELEMENT

a

CM: (%a.content;)
AT: %attrs;, %focus;, charset, type, name, href, hreflang, rel, rev, shape, cords, target

OBJECT ELEMENT

object

CM: (#PCDATA | param | %block; | form | %inline; | %misc;)*
AT: %attrs;, declare, classid, codebase, data, type, codetype, archive, standby, height, width, usemap, name, tabindex, align, border, hspace, vspace

param

CM: EMPTY
AT: id, name, value, valuetype, type

JAVA APPLET

applet

CM: (#PCDATA | param | %block; | form | %inline; | %misc;)
AT: %coreattrs;, codebase, archive, code, object, alt, name, width, height, align, hspace, vspace

IMAGES

img

CM: EMPTY
AT: %attrs;, src, alt, name, longdesc, height, width, usemap, ismap, align, border, hspace, vspace

CLIENT-SIDE IMAGE MAPS

map

CM: ((%block; | form | %misc;)+ | area+)
AT: %i18n;, %events;, id, class, style, title, name

area

CM: EMPTY
AT: %attrs;, %focus;, shape, coords, href, nohref, alt, target

FORMS

form

CM: (%form.content;)
AT: %attrs;, action, method, name, enctype, onsubmit, onreset, accept, accept-charset, target

label

CM: (%Inline;)
AT: %attrs;, for, accesskey, onfocus, onblur

input

CM: EMPTY
AT: %attrs;, %focus;, type, name, value, checked, disabled, readonly, size, maxlength, src, alt, usemap, onselect, onchange, accept, align

select

CM: (optgroup | option)+
AT: %attrs;, name, size, multiple, disabled, tabindex, onfocus, onblur, onchange

optgroup

CM: (option)+
AT: %attrs;, disabled, label

option

CM: (#PCDATA)
AT: %attrs;, selected, disabled, label, value

textarea

CM: (#PCDATA)
AT: %attrs;, %focus;, name, rows, cols, disabled, readonly, onselect, onchange

fieldset

CM: (#PCDATA | legend | %block; | form | %inline; | %misc;)*
AT: %attrs;

legend

CM: (%Inline;)

AT: %attrs;, accesskey, align

button

CM: (%button.content;)

AT: %attrs;, %focus;, name, value, type, disabled

isindex

CM: EMPTY

AT: %coreattrs;, %i18n;, prompt

TABLES

%cellhalign; | **%cellvalign;**

align, char, charoff

table

CM: (caption?,
(col* | colgroup*),
thead?, tfoot?,
(tbody+ | tr+))

AT: %attrs;, summary, width, border, frame, rules, cellspacing,
cellpadding, align, bgcolor

caption

CM: (%Inline;)

AT: %attrs;, align

colgroup

CM: (col)*

AT: %attrs;, span, width,
%cellhalign;, %cellvalign;

col

CM: EMPTY

AT: %attrs;, span, width,
%cellhalign;, %cellvalign;

thead, tfoot, tbody

CM: (tr)+

AT: %attrs;, %cellhalign;,
%cellvalign;

tr

CM: (th | td)+

AT: %attrs;, %cellhalign;,
%cellvalign;, bgcolor

th, td

CM: (%Flow;)

AT: %attrs;, abbr, axis,
headers, scope, rowspan,
colspan, %cellhalign;,
%cellvalign;, nowrap,
bgcolor, width, height

PARAMETER ENTITIES (TEXT ELEMENTS)

%special.extra

object | applet | img | map |
iframe

%special.basic;

br | span | bdo

%special;

%special.basic; |
%special.extra;

%fontstyle.extra;

big | small | font | basefont

%fontstyle.basic;

tt | i | b | u | s | strike

%fontstyle;

%fontstyle.basic; |
%fontstyle.extra;

%inline.forms;

input | select | textarea |
label | button

%phrase.extra;

sub | sup

%phrase.basic;

em | strong | dfn | code | q |
samp | kbd | var | cite | abbr |
acronym

%phrase;

%phrase.basic; | %phrase.extra;

%misc.inline;

ins | del | script

%misc;

noscript | %misc.inline;

%inline;

a | %special; | %fontstyle; |
%phrase; | %inline.forms;

%Inline;

(#PCDATA | %inline; |
%misc.inline;)*

PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)

%heading;

h1 | h2 | h3 | h4 | h5 | h6

%blocktext;

pre | hr | blockquote | address | center

%lists;

ul | ol | dl | menu | dir

%block;

p | %heading; | div | %lists; | %blocktext; | isindex | fieldset |
table

%Flow;

(#PCDATA | %block; | form | %inline; | %misc;)*

PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)

%a.content;

(#PCDATA | %special; | %fontstyle; | %phrase; | %inline.forms; |
%misc.inline;)*

%pre.content;

(#PCDATA | a | %special.basic; | %fontstyle.basic; | %phrase.basic; |
%inline.forms; | %misc.inline;)*

%form.content;

(#PCDATA | %block; | %inline; | %misc;)*

%button.content;

(#PCDATA | p | %heading; | div | %lists; | %blocktext; | table | br |
span | bdo | object | applet | img | map | %fontstyle; | %phrase; |
%misc;)*

PARAMETER ENTITIES (GENERIC ATTRIBUTES)

%events;

onclick, ondblclick, onmousedown, onmouseup, onmouseover, onmouseout,
onmousemove, onmouseover, onkeypress, onkeydown, onkeyup

%coreattrs;

id, class, style, title

%i18n;

lang, xml:lang, dir

%focus;

accesskey, tabindex, onfocus, onblur

%TextAlign;

align

%attrs;

%coreattrs;, %i18n;, %events;

CHARACTER ENTITY SETS

Latin-1 characters

acute, Aacute, acirc, Acirc, acute, aelig, Aelig, agrave, Agrave,
aring, Aring, atilde, Atilde, auuml, auuml, brvbar, ccedil, Ccedil,
cedil, cent, copy, curren, deg, divide, eacute, Eacute, ecirc,
Ecirc, egrave, Egrave, eth, ETH, euuml, Euuml, frac12, frac14, frac34,
iacute, Iacute, icirc, Icirc, iexcl, igrave, Igrave, igoth, iuml,
Iuml, laquo, macr, micro, middot, nbsp, not, ntilde, Ntilde, oacute,
Oacute, ocirc, Ocirc, ograve, Ograve, ordf, ordm, oslash, Oslash,
otilde, Otilde, ouuml, Ouuml, para, plusmn, pound, raquo, reg, sect,
shy, sup1, sup2, sup3, szlig, thorn, THORN, times, uacute, Uacute,
ucirc, Ucirc, ugrave, Ugrave, uml, uuml, Uuml, yacute, Yacute, yen,
yuml

Special characters

amp, apos, bdquo, circ, dagger, Dagger, emsp, ensp, euro, gt, ldquo,
lrm, lsaquo, lsquo, lt, mdash, ndash, oelig, Oelig, permil, quot,
rdquo, rlm, rsquo, sbquo, scaron, Scaron, thinsp, tilde,
Yuml, zwj, zwnj

Symbols

alefsym, alpha, Alpha, and, ang, asymp, beta, Beta, bull, cap, chi,
Chi, clubs, cong, crarr, cup, darr, dArr, delta, Delta, diams,
empty, epsilon, Epsilon, equiv, eta, Eta, exist, fnof, forall,
frac1, gamma, Gamma, ge, harr, hArr, hearts, hellip, image, infin,
int, iota, Iota, isin, Kappa, Kappa, lambda, Lambda, lang, larr,
lArr, lceil, le, lfloor, lowast, loz, minus, mu, Mu, nabla, ne, ni,
notin, nsub, nu, Nu, oline, omega, Omega, omicron, Omicron, oplus,
or, otimes, part, perp, phi, Phi, pi, Pi, piv, prime, Prime, prod,
prop, psi, Psi, radic, rang, rarr, rArr, rceil, real, rfloor, rho,
Rho, sdot, sigma, Sigma, sigmaf, sim, spades, sub, sube, sum, sup,
supe, tau, Tau, there4, theta, Theta, thetasym, trade, uarr, uArr,
upsih, upsilon, Upsilon, weierp, xi, Xi, zeta, Zeta



QUICK REFERENCE

XHTML

Version 1.0-Transitional

<http://www.w3.org/TR/xhtml1/>

Table of Contents:

- FORMAL PUBLIC IDENTIFIER
- DOCUMENT STRUCTURE
- DOCUMENT HEAD
- FRAMES
- DOCUMENT BODY
- PARAGRAPHS
- HEADINGS
- ADDRESS
- LISTS
- HORIZONTAL RULE
- PREFORMATTED TEXT
- BLOCK-LIKE QUOTES
- TEXT ALIGNMENT
- INSERTED/DELETED TEXT
- ANCHOR ELEMENT
- INLINE ELEMENTS
- OBJECT ELEMENT
- JAVA APPLET
- IMAGES
- CLIENT-SIDE IMAGE MAPS
- FORMS
- TABLES
- PARAMETER ENTITIES (TEXT ELEMENTS)
- PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)
- PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)
- PARAMETER ENTITIES (GENERIC ATTRIBUTES)
- CHARACTER ENTITY SETS