

## FORMAL PUBLIC IDENTIFIER

```
<!DOCTYPE html
PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

## DOCUMENT STRUCTURE

### html

CM: (head, body)  
AT: %i18;, id, xmlns

## DOCUMENT HEAD

### %head.misc

(script | style | meta | link | object | isindex)

### head

CM: (%head.misc;,  
((title, %head.misc;,  
(base, %head.misc;)? ) |  
(base, %head.misc;,  
(title, %head.misc;))) )  
AT: %i18n;, id, profile

### title

CM: (#PCDATA)  
AT: %i18n;, id

### base

CM: EMPTY  
AT: id, href, target

### meta

CM: EMPTY  
AT: %i18n;, id, http-equiv, name, content, scheme

### link

CM: EMPTY  
AT: %attrs;, charset, href, hreflang, type, rel, rev, media, target

### style

CM: (#PCDATA)  
AT: %i18n;, id, type, media, title, xml:space

### script

CM: (#PCDATA)  
AT: id, charset, type, language, src, defer, xml:space

### noscript

CM: (%Flow;)  
AT: %attrs;

## FRAMES

### iframe

CM: (%Flow;)  
AT: marginheight, longdesc, title, scrolling, width, frameborder,  
name, style, height, src, class, align, id, marginwidth

### noframes

CM: (%Flow;)  
CM: %attrs;

## DOCUMENT BODY

### body

CM: (%Flow;)  
AT: %attrs;, onload, onunload,  
background, bgcolor, text,  
link, vlink, alink

### div

CM: (%Flow;)  
AT: %attrs;, %TextAlign;

## PARAGRAPHS

### p

CM: (%Inline;)  
AT: %attrs;, %TextAlign;

## HEADINGS

### h1, h2, h3, h4, h5, h6

CM: (%Inline;)  
AT: %attrs;, %TextAlign;

## ADDRESS

### address

CM: (#PCDATA | %inline; / %misc.inline / p)  
AT: %attrs;

## LISTS

### ul

CM: (li)+  
AT: %attrs;, type, compact

### ol

CM: (li)+  
AT: %attrs;, type, compact,  
start

### menu, dir

CM: (li)+  
AT: %attrs;, compact

### li

CM: (%Flow;)  
AT: %attrs;, type, value

### dl

CM: (dt | dd)+  
AT: %attrs;, compact

### dt

CM: (%Inline;)  
AT: %attrs;

### dd

CM: (%Flow;)  
AT: %attrs;

## HORIZONTAL RULE

### hr

CM: EMPTY  
AT: %attrs;, align, noshade, size, width

## PREFORMATTED TEXT

### pre

CM: (%pre.content;)  
AT: %attrs;, width, xml:space

## BLOCK-LIKE QUOTES

### blockquote

CM: (%Flow;)  
AT: %attrs;, cite

## TEXT ALIGNMENT

### center

CM: (%Flow;)  
AT: %attrs;

## INSERTED/DELETED TEXT

### ins, del

CM: (%Flow;)  
AT: %attrs;, cite, datetime

## ANCHOR ELEMENT

### a

CM: (%a.content;)  
AT: %attrs;, %focus;, charset, type, name, href, hreflang, rel,  
rev, shape, cords, target

## INLINE ELEMENTS

### span, em, strong, dfn, code, samp, kbd, var, cite, abbr, acronym, sub, sup, tt, i, b, big, small, u, s, strike

CM: (%Inline;)  
AT: %attrs;

### bdo

CM: (%Inline;)  
AT: %coreattrs;, %events;, lang,  
xml:lang, dir

### br

CM: EMPTY  
AT: %coreattrs;, clear

### q

CM: (%Inline;)  
AT: %attrs;, cite

### basefont

CM: EMPTY  
AT: id, size, color, face

### font

CM: (%Inline;)  
AT: %coreattrs;, %i18n;, size,  
color, face

## OBJECT ELEMENT

### object

CM: (#PCDATA | param | %block; | form | %inline; | %misc;)\*  
AT: %attrs;, declare, classid, codebase, data, type, codetype,  
archive, standby, height, width, usemap, name, tabindex, align,  
border, hspace, vspace

### param

CM: EMPTY  
AT: id, name, value, valuetype, type

## JAVA APPLET

### applet

CM: (#PCDATA | param | %block; | form | %inline; | %misc;)  
AT: %coreattrs;, codebase, archive, code, object, alt, name, width,  
height, align, hspace, vspace

## IMAGES

### img

CM: EMPTY  
AT: %attrs;, src, alt, name, longdesc, height, width, usemap,  
ismap, align, border, hspace, vspace

## CLIENT-SIDE IMAGE MAPS

### map

CM: ((%block; | form | %misc;)+ | area+)  
AT: %i18n;, %events;, id, class, style, title, name

### area

CM: EMPTY  
AT: %attrs;, %focus;, shape, coords, href, nohref, alt, target

## FORMS

### form

CM: (%form.content;)  
AT: %attrs;, action, method, name, enctype, onsubmit, onreset,  
accept, accept-charset, target

### label

CM: (%Inline;)  
AT: %attrs;, for, accesskey, onfocus, onblur

### input

CM: EMPTY  
AT: %attrs;, %focus;, type, name, value, checked, disabled,  
readonly, size, maxlength, src, alt, usemap, onselect,  
onchange, accept, align

### select

CM: (optgroup | option)+  
AT: %attrs;, name, size, multiple, disabled, tabindex, onfocus,  
onblur, onchange

### optgroup

CM: (option)+  
AT: %attrs;, disabled, label

### option

CM: (#PCDATA)  
AT: %attrs;, selected, disabled, label, value

### textarea

CM: (#PCDATA)  
AT: %attrs;, %focus;, name, rows, cols, disabled, readonly,  
onselect, onchange

### fieldset

CM: (#PCDATA | legend | %block; | form | %inline; | %misc;)\*  
AT: %attrs;

### legend

CM: (%Inline;)  
AT: %attrs;, accesskey, align

### button

CM: (%button.content;)  
AT: %attrs;, %focus;, name, value, type, disabled

### isindex

CM: EMPTY  
AT: %coreattrs;, %i18n;, prompt

## TABLES

<b>%cellalign;</b>
align, char, charoff
<b>%cellvalign;</b>
valign
<b>table</b>
CM: (caption?, (col*   colgroup*), thead?, tfoot?, (tbody+   tr+))
AT: %attrs;, summary, width, border, frame, rules, cellspacing, cellpadding, align, bgcolor
<b>caption</b>
CM: (%Inline;)
AT: %attrs;, align
<b>colgroup</b>
CM: (col)*
AT: %attrs;, span, width, %cellalign;, %cellvalign;
<b>col</b>
CM: EMPTY
AT: %attrs;, span, width, %cellalign;, %cellvalign;
<b>thead, tfoot, tbody</b>
CM: (tr)+
AT: %attrs;, %cellalign;, %cellvalign;
<b>tr</b>
CM: (th   td)+
AT: %attrs;, %cellalign;, %cellvalign;, bgcolor
<b>th, td</b>
CM: (%Flow;)
AT: %attrs;, abbr, axis, headers, scope, rowspan, colspan, %cellalign;, %cellvalign;, nowrap, bgcolor, width, height

## PARAMETER ENTITIES (TEXT ELEMENTS)

<b>%special.extra</b>	<b>%phrase.extra;</b>
object   applet   img   map   iframe	sub   sup
<b>%special.basic;</b>	<b>%phrase.basic;</b>
br   span   bdo	em   strong   dfn   code   q   samp   kbd   var   cite   abbr   acronym
<b>%special;</b>	<b>%phrase;</b>
%special.basic;   %special.extra;	%phrase.basic;   %phrase.extra;
<b>%fontstyle.extra;</b>	<b>%misc.inline;</b>
big   small   font   basefont	ins   del   script
<b>%fontstyle.basic;</b>	<b>%misc;</b>
tt   i   b   u   s   strike	noscript   %misc.inline;
<b>%fontstyle;</b>	<b>%inline;</b>
%fontstyle.basic;   %fontstyle.extra;	a   %special;   %fontstyle;   %phrase;   %inline.forms;
<b>%inline.forms;</b>	<b>%IInline;</b>
input   select   textarea   label   button	(#PCDATA   %inline;   %misc.inline;)*

## PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)

<b>%heading;</b>	<b>%lists;</b>
h1   h2   h3   h4   h5   h6	ul   ol   dl   menu   dir
<b>%blocktext;</b>	
pre   hr   blockquote   address   center   noframes	

<b>%block;</b>
p   %heading;   div   %lists;   %blocktext;   isindex   fieldset   table
<b>%Flow;</b>
(#PCDATA   %block;   form   %inline;   %misc;)*

## PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)

<b>%a.content;</b>
(#PCDATA   %special;   %fontstyle;   %phrase;   %inline.forms;   %misc.inline;)*
<b>%pre.content;</b>
(#PCDATA   a   %special.basic;   %fontstyle.basic;   %phrase.basic;   %inline.forms;   %misc.inline;)*
<b>%form.content;</b>
(#PCDATA   %block;   %inline;   %misc;)*
<b>%button.content;</b>
(#PCDATA   p   %heading;   div   %lists;   %blocktext;   table   br   span   bdo   object   applet   img   map   %fontstyle;   %phrase;   %misc;)*

## PARAMETER ENTITIES (GENERIC ATTRIBUTES)

<b>%events;</b>	
onclick, ondblclick, onmousedown, onmouseup, onmouseover, onmousemove, onmouseout, onkeypress, onkeydown, onkeyup	
<b>%coreattrs;</b>	<b>%TextAlign;</b>
id, class, style, title	align
<b>%i18n;</b>	<b>%attrs;</b>
lang, xml:lang, dir	%coreattrs;, %i18n;, %events;
<b>%focus;</b>	
accesskey, tabindex, onfocus, onblur	

## CHARACTER ENTITY SETS

<b>Latin-1 characters</b>
aacute, Aacute, acirc, Acirc, acute, aelig, Aelig, agrave, Agrave, aring, Aring, atilde, Atilde, auml, Auml, brvbar, ccedil, Ccedil, cedil, cent, copy, curren, deg, divide, eacute, Eacute, ecirc, Ecirc, egrave, Egrave, eth, ETH, euml, Euml, frac12, frac14, frac34, iacute, Iacute, icirc, Icirc, iexcl, igrave, Igrave, iquest, iuml, Iuml, laquo, macr, micro, middot, nbsp, not, ntilde, Ntilde, oacute, Oacute, ocirc, Ocirc, ograve, Ograve, ordf, ordm, oslash, Oslash, otilde, Otilde, ouml, Ouml, para, plusmn, pound, raquo, reg, sect, shy, sup1, sup2, sup3, szlig, thorn, THORN, times, uacute, Uacute, ucirc, Ucirc, ugrave, Ugrave, uml, uuml, Uuml, yacute, Yacute, yen, yuml
<b>Special characters</b>
amp, apos, bdquo, circ, dagger, Dagger, emsp, ensp, euro, gt, ldquo, lrm, lsquo, lsquo, lt, mdash, ndash, oelig, Oelig, permil, quot, rdquo, rlm, rsquo, rsquo, sbquo, scaron, Scaron, thinsp, tilde, Yuml, zwj, zwnj
<b>Symbols</b>
alefsym, alpha, Alpha, and, ang, asymp, beta, Beta, bull, cap, chi, Chi, clubs, cong, crarr, cup, darr, dArr, delta, Delta, diams, empty, epsilon, Epsilon, equiv, eta, Eta, exist, fnof, forall, frasl, gamma, Gamma, ge, harr, hArr, hearts, hellip, image, infin, int, iota, Iota, isin, Kappa, Kappa, lambda, Lambda, lang, larr, lArr, lceil, le, lfloor, lowast, loz, minus, mu, Mu, nabla, ne, ni, notin, nsub, nu, Nu, oline, omega, Omega, omicron, Omicron, oplus, or, otimes, part, perp, phi, Phi, pi, Pi, piv, prime, Prime, prod, prop, psi, Psi, radic, rang, rarr, rArr, rceil, real, rfloor, rho, Rho, sdot, sigma, Sigma, sigmaf, sim, spades, sub, sube, sum, sup, supe, tau, Tau, there4, theta, Theta, thetasym, trade, uarr, uArr, upsil, Upsilon, Upsilon, weierp, xi, Xi, zeta, Zeta



# QUICK REFERENCE

## XHTML

Version 1.0-Transitional

<http://www.w3.org/TR/xhtml1/>

### Table of Contents:

- FORMAL PUBLIC IDENTIFIER
- DOCUMENT STRUCTURE
- DOCUMENT HEAD
- FRAMES
- DOCUMENT BODY
- PARAGRAPHS
- HEADINGS
- ADDRESS
- LISTS
- HORIZONTAL RULE
- PREFORMATTED TEXT
- BLOCK-LIKE QUOTES
- TEXT ALIGNMENT
- INSERTED/DELETED TEXT
- ANCHOR ELEMENT
- INLINE ELEMENTS
- OBJECT ELEMENT
- JAVA APPLETS
- IMAGES
- CLIENT-SIDE IMAGE MAPS
- FORMS
- TABLES
- PARAMETER ENTITIES (TEXT ELEMENTS)
- PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)
- PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)
- PARAMETER ENTITIES (GENERIC ATTRIBUTES)
- CHARACTER ENTITY SETS