

FORMAL PUBLIC IDENTIFIER

```
<!DOCTYPE html
PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
```

DOCUMENT STRUCTURE

html

CM: (head, body)
AT: %i18;, id, xmlns

DOCUMENT HEAD

%head.misc

(script | style | meta | link | object | isindex)

head

CM: (%head.misc,
((title, %head.misc,
(base, %head.misc;)? |
(base, %head.misc;
(title, %head.misc;))))
AT: %i18n;, id, profile

title

CM: (#PCDATA)
AT: %i18n;, id

base

CM: EMPTY
AT: href, id

meta

CM: EMPTY
AT: %i18n;, id, http-equiv, name, content, scheme

link

CM: EMPTY
AT: %attrs;, charset, href, hreflang, type, rel, rev, media

style

CM: (#PCDATA)
AT: %i18n;, id, type, media, title, xml:space

script

CM: (#PCDATA)
AT: id, charset, type, src, defer, xml:space

noscript

CM: (%Block;)
AT: %attrs;

DOCUMENT BODY

body

CM: (%Block;)
AT: onload, onunload

div

CM: (%Flow;)
AT: %attrs;

PARAGRAPHS

p

CM: (%Inline;)
AT: %attrs;

HEADINGS

h1, h2, h3, h4, h5, h6

CM: (%Inline;)
AT: %attrs;

LISTS

ul, ol

CM: (li)+
AT: %attrs;

li

CM: (%Flow;)
AT: %attrs;

dl

CM: (dt | dd)+
AT: %attrs;

dt

CM: (%Inline;)
AT: %attrs;

dd

CM: (%Flow;)
AT: %attrs;

ADDRESS

address

CM: (%Inline;)
AT: %attrs;

HORIZONTAL RULE

hr

CM: EMPTY
AT: %attrs;

PREFORMATTED TEXT

pre

CM: (%pre.content;)
AT: %attrs;, xml:space

BLOCK-LIKE QUOTES

blockquote

CM: (%Block;)
AT: %attrs;, cite

INSERTED/DELETED TEXT

ins, del

CM: (%Flow;)
AT: %attrs;, cite, datetime

ANCHOR ELEMENT

a

CM: (%a.content;)
AT: %attrs;, %focus;, charset, type, name, href, hreflang, rel, rev, shape, coords

INLINE ELEMENTS

span, em, strong, dfn, code, samp, kbd, var, cite, abbr, acronym, sub, sup, tt, i, b, big, small

CM: (%Inline;)
AT: %attrs;

bdo

CM: (%Inline;)
AT: %coreattrs;, %events;, lang, xml:lang, dir

br

CM: EMPTY
AT: %coreattrs;

q

CM: (%Inline;)
AT: %attrs;, cite

OBJECT ELEMENT

object

CM: (#PCDATA|param|block;|form|inline;|misc;)*
AT: %attrs;, declare, classid, codebase, data, type, codetype, archive, standby, height, width, usemap, name, tabindex

param

CM: EMPTY
AT: id, name, value, valuetype, type

IMAGES

img

CM: EMPTY
AT: %attrs;, src, alt, longdesc, height, width, usemap, ismap

CLIENT-SIDE IMAGE MAPS

map

CM: ((block; | form | %misc;)+ | area+)
AT: %i18n;, %events;, id, class, style, title, name

area

CM: EMPTY
AT: %attrs;, %focus;, shape, coords, href, nohref, alt

FORMS

form

CM: (%form.content;)
AT: %attrs;, action, method, enctype, onsubmit, onreset, accept, accept-charset

label

CM: (%Inline;)
AT: %attrs;, for, accesskyy, onfocus, onblur

input

CM: EMPTY
AT: %attrs;, %focus;, type, name, value, checked, disabled, readonly, size, maxlength, src, alt, usemap, onselect, onchange, accept

select

CM: (optgroup | option)+
AT: %attrs;, name, size, multiple, disabled, tabindex, onfocus, onblur, onchange

optgroup

CM: (option)+
AT: %attrs;, disabled, label

option

CM: (#PCDATA)
AT: %attrs;, selected, disabled, label, value

textarea

CM: (#PCDATA)
AT: %attrs;, %focus;, name, rows, cols, disabled, readonly, onselect, onchange

fieldset

CM: (#PCDATA | legend | %block; | form | %inline; | %misc;)*
AT: %attrs;

legend

CM: (%Inline;)
AT: %attrs;, accesskey

button

CM: (%button.content;)
AT: %attrs;, %focus;, name, value, type, disabled

TABLES

%cellhalign;

align, char, charoff

%cellvalign;

valign

table

CM: (caption?,
(col* | colgroup*),
thead?, tfoot?,
(tbody+ | tr+))
AT: %attrs;, summary, width, border, frame, rules, cellspacing,
cellpadding

caption

CM: (%Inline;)
AT: %attrs;

colgroup

CM: (col)*
AT: %attrs;, span, width, %cellhalign;, %cellvalign;

col

CM: EMPTY
AT: %attrs;, span, width, %cellhalign;, %cellvalign;

thead, tfoot, tbody

CM: (tr)+
AT: %attrs;, %cellhalign;, %cellvalign;

tr

CM: (th | td)+
AT: %attrs;, %cellhalign;, %cellvalign;

th, td

CM: (%Flow;)
AT: %attrs;, abbr, axis, headers, scope, rowspan, colspan,
%cellhalign;, %cellvalign;

PARAMETER ENTITIES (TEXT ELEMENTS)

%special.pre;

br | span | bdo | map

%special;

%special.pre; | object | img

%fontstyle;

tt | i | b | big | small

%phrase;

em | strong | dfn | code | q | samp | kbd | var | cite | abbr |
acronym | sub | sup

%inline.forms;

input | select | textarea | label | button

%misc.inline;

ins | del | script

%misc;

noscript | %misc.inline;

%inline;

a | %special; | %fontstyle; | %phrase; | %inline.forms;

%Inline;

(#PCDATA | %inline; | %misc.inline;)*

PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)

%heading;

h1 | h2 | h3 | h4 | h5 | h6

%lists;

ul | ol | dl

%blocktext;

pre | hr | blockquote | address

%block;

p | %heading; | div | %lists; | %blocktext; | fieldset | table

%Block;

p | %heading; | div | %lists; | %blocktext; | fieldset | table

%Flow;

(#PCDATA | %block; | form | %inline; | %misc;)*

PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)

%a.content;

(#PCDATA | %special; | %fontstyle; | %phrase; | %inline.forms; |
%misc.inline;)*

%pre.content;

(#PCDATA | a | %fontstyle; | %phrase; | %special.pre; |
%misc.inline; | %inline.forms;)*

%form.content;

(%block; | %misc;)*

%button.content;

(#PCDATA | p | %heading; | div | %lists; | %blocktext; | table |
%special; | %fontstyle; | %phrase; | %misc;)*

PARAMETER ENTITIES (GENERIC ATTRIBUTES)

%coreattrs;

id, class, style, title

%i18n;

lang, xml:lang, dir

%events;

onclick, ondblclick, onmousedown, onmouseup, onmouseover,
onmousemove, onmouseout, onkeypress, onkeydown, onkeyup

%focus;

accesskey, tabindex, onfocus, onblur

%attrs;

%coreattrs;, %i18n;, %events;

CHARACTER ENTITY SETS

Latin-1 characters

aaacute, Aacute, acirc, Acirc, acute, aelig, Aelig, agrave, Agrave,
aring, Aring, atilde, Atilde, auml, Auml, brvbar, ccedil, Ccedil,
cedil, cent, copy, curren, deg, divide, eacute, Eacute, ecirc,
Ecirc, egrave, Egrave, eth, ETH, euml, Euml, frac12, frac14, frac34,
iacute, Iacute, icirc, Icirc, iexcl, igrave, Igrave, iquest, iuml,
Iuml, laquo, macr, micro, middot, nbsp, not, ntilde, Ntilde, oacute,
Oacute, ocirc, Ocirc, ograve, Ograve, ordf, ordm, oslash, Oslash,
otilde, Otilde, ouml, Ouml, para, plusmn, pound, raquo, reg, sect,
shy, supl, sup2, sup3, szlig, thorn, THORN, times, uacute, Uacute,
ucirc, Ucirc, ugrave, Ugrave, uml, uuml, Uuml, yacute, Yacute, yen,
yuml

Special characters

amp, apos, bdquo, circ, dagger, Dagger, emsp, ensp, euro, gt, ldquo,
lrm, lsaquo, lsquo, lt, mdash, ndash, oelig, Oelig, permil, quot,
rdquo, rlm, rsaquo, rsquo, sbquo, scaron, Scaron, thinsp, tilde,
Yuml, zwj, zwnj

Symbols

alefsym, alpha, Alpha, and, ang, asymp, beta, Beta, bull, cap, chi,
Chi, clubs, cong, crarr, cup, darr, dArr, delta, Delta, diams,
empty, epsilon, Epsilon, equiv, eta, Eta, exist, fnof, forall,
frasl, gamma, Gamma, ge, harr, hArr, hearts, hellip, image, infin,
int, iota, Iota, isin, kappa, Kappa, lambda, Lambda, lang, larr,
lArr, lceil, le, lfloor, lowast, loz, minus, mu, Mu, nabla, ne, ni,
notin, nsub, nu, Nu, oline, omega, Omega, omicron, Omicron, oplus,
or, otimes, part, perp, phi, Phi, pi, Pi, piv, prime, Prime, prod,
prop, psi, Psi, radic, rang, rarr, rArr, rceil, real, rfloor, rho,
Rho, sdot, sigma, Sigma, sigmaf, sim, spades, sub, sube, sum, sup,
supe, tau, Tau, there4, theta, Theta, thetasym, trade, uarr, uArr,
upsih, upsilon, Upsilon, weierp, xi, Xi, zeta, Zeta



QUICK REFERENCE

XHTML Version 1.0-Strict

<http://www.w3.org/TR/xhtml1/>

Table of Contents:

FORMAL PUBLIC IDENTIFIER
DOCUMENT STRUCTURE
DOCUMENT HEAD
DOCUMENT BODY
PARAGRAPHS
HEADINGS
LISTS
ADDRESS
HORIZONTAL RULE
PREFORMATTED TEXT
BLOCK-LIKE QUOTES
INSERTED/DELETED TEXT
ANCHOR ELEMENT
INLINE ELEMENTS
OBJECT ELEMENT
IMAGES
CLIENT-SIDE IMAGE MAPS
FORMS
TABLES
PARAMETER ENTITIES (TEXT ELEMENTS)
PARAMETER ENTITIES (BLOCK LEVEL ELEMENTS)
PARAMETER ENTITIES (CONTENT MODELS FOR EXCLUSION)
PARAMETER ENTITIES (GENERIC ATTRIBUTES)
CHARACTER ENTITY SETS

Benjamin Jung
Trinity College Dublin,
Ireland

Benjamin.Jung@cs.tcd.ie
<http://www.cs.tcd.ie/Benjamin.Jung/>